

Power Supply Filter Components: VIIP Empowers New Energy EV Charging and ESS Inverters

VIIP 维爱普®

POWER SUPPLY FILTER COMPONENTS

VIIP Empowers New Energy
EV Charging and ESS Inverters



Shenzhen, Guangdong Oct 13, 2026 ([Issuewire.com](https://www.issuewire.com)) - Commercializing high-power electric vehicle (EV) DC fast-charging stations and utility-scale energy storage systems (ESS) requires managing severe electromagnetic environments across high-voltage direct-current buses and grid-tied power conversion systems (PCS). High-power charging dispensers and bi-directional storage inverters adopt high-speed insulated-gate bipolar transistors (IGBTs) and silicon carbide (SiC) MOSFETs operating

across high-voltage direct-current buses up to 500VDC. Rapid semiconductor switching generates steep voltage transitions (dv/dt) and high-frequency current ripple (di/dt) along DC power lines, requiring coordinated filtering to maintain battery management system (BMS) telemetry accuracy, analog sensor precision, and grid-tie power quality. Deploying specialized [surface mount single phase EMI filters 500VDC](#) alongside heavy-duty DC power line filters establishes essential conducted emission suppression and electrical isolation across renewable energy infrastructure. Shenzhen [VIIP Electronics Co., Ltd. \(VIIP\)](#) manufactures high-performance power supply filter components engineered to protect clean energy systems from electromagnetic disturbances.

High-Voltage DC Bus Dynamics and Signal Isolation Requirements

Operating at continuous direct-current potentials of 500VDC and above introduces complex noise propagation pathways between utility grid interconnections and chemical energy storage arrays. In the VIIP power filter architecture, mitigating these high-voltage disturbances requires coordinated low-pass filtering. High-frequency active front-end rectifiers and isolated DC/DC switching topologies generate steep voltage transitions and high current ripple that propagate simultaneously in upstream and downstream directions. Upstream noise currents travel toward AC distribution lines, impacting total harmonic distortion and grid compliance. Downstream high-frequency ripple circulates along DC battery cables, coupling capacitively into digital telemetry lines, analog-to-digital current sensors, and high-precision battery monitoring boards. Mitigating these disturbances requires establishing distinct low-pass filtering stages at both primary AC utility terminals and secondary DC distribution buses to maintain signal integrity and electrical isolation.

Architecture and Performance Parameters of the VIP4-1A-06 Surface Mount Filter

Precision measurement circuits, controller boards, and isolated telemetry interfaces within EV chargers and ESS cabinets require compact, board-level EMI suppression capable of withstanding high DC operating potentials. The VIIP VIP4-1A-06 exemplifies this high-density filtering engineering. Designed for measuring instruments, industrial control cards, and medical electronics, the VIP4-1A-06 supports a continuous rated current of 6A and operates at a working potential of 500VDC with verified dielectric withstand ratings of 1760VDC line-to-line and 2000VAC line-to-ground.

The component is engineered with a standard 50-Ohm characteristic impedance match and delivers wideband insertion loss performance spanning 30dB to 100dB across the conducted spectrum. Packaged in a compact metallic shielding casing supporting versatile terminal, lead, and surface-mount configurations, the VIP4-1A-06 shields sensitive current sensors and microcontroller power inputs from adjacent high-power switching transients. Internally, the low-pass topology incorporates symmetrical dual-winding common mode chokes paired with X/Y safety capacitors and damping discharge elements. This passive configuration attenuates high-frequency ripple and fast transient spikes across power feeds, helping prevent baseline noise elevation and false triggering in sensitive measurement circuits such as battery telemetry front-ends and ADC reference channels.

High-Power DC Power Line Filters and Three-Phase Conversion Matrix

While board-level filters like the VIP4-1A-06 protect localized electronics, primary power paths in DC fast chargers require heavy-duty power line filters. VIIP manufactures an extensive portfolio of DC EMI filters rated for nominal operating potentials from 0 to 250VDC and 500VDC, with continuous current handling spanning from 1A up to 200A.

These units integrate distributed-gap powder magnetic cores that maintain high saturation flux densities

exceeding 1.2 Tesla under continuous direct-current bias, preventing magnetic saturation under full-load operation. In utility-scale energy storage power conversion systems and multi-dispenser EV charging plazas, complementary three-phase AC filters operate at 380VAC, 480VAC, and 600VAC, providing current handling scaling up to 3000A, line-to-ground dielectric withstand ratings up to 2250VDC, and multi-stage insertion loss attenuation from 60dB to 100dB. The combination of coordinated AC input filtering and DC bus filtering establishes an effective multi-tier barrier against grid harmonics and inverter switching noise.

Manufacturing Scale Across Three Production Bases and Global Regulatory Alignment

Scaling clean energy infrastructure requires verified component repeatability and dependable delivery timelines. Shenzhen VIIP Electronics Co., Ltd. operates three modern manufacturing bases located in Huizhou, Bozhou, and Huzhou. These facilities integrate automated powder pressing kilns, computerized coil winding stations, and high-speed encapsulation lines. This multi-base manufacturing footprint supports reliable volume deliveries for global energy storage developers and charging station manufacturers.

The filter catalog holds valid international safety and quality certifications across UL, TUV, CE, and CQC standards, with complete material compliance aligned with European RoHS 2.0 and REACH environmental directives. Vacuum epoxy encapsulation employing UL94 V-0 flame-retardant polymers facilitates internal heat dissipation and stabilizes mechanical components against intense industrial vibration. Every production batch undergoes 100% factory dielectric withstand testing, insulation resistance screening exceeding 100 Megaohms (100 MOhm), and earth discharge current verification, supported by a standard one-year warranty upon delivery.

Turnkey Filtering Integration and Engineering Application Summary

Deploying dedicated VIIP power supply filter components across EV charging infrastructures and ESS plants yields concrete operational returns:

Preserving Telemetry Accuracy: Suppressing DC bus ripple prevents false tripping of battery management systems and maintains precision state-of-charge measurements.

Mitigating High-Frequency Parasitic Heating: Filtering high-frequency ripple currents reduces internal resistive heating in battery cells and DC-link film capacitors, extending subsystem service life.

Accelerating Worldwide Certification: Verified insertion loss performance enables equipment builders to pass international grid-tie and EMC standards on initial lab submission.

Modern DC fast-charging dispensers delivering up to 350kW to 480kW power output require continuous thermal management and durable transient protection. In these ultra-fast charging topologies, liquid-cooled DC cables and high-frequency silicon carbide power stacks produce intense common-mode noise across the 150kHz to 30MHz conducted band. Installing specialized VIIP dual-stage DC filters directly adjacent to the output contactors blocks high-frequency common-mode noise from radiating into vehicle chassis grounds, preventing communication interruptions between the charger controller and the on-board vehicle electronic control unit (ECU).

In addition, in commercial microgrid battery storage systems paired with commercial rooftop solar arrays, bidirectional inverters create dynamic harmonic interactions when switching between grid-forming and grid-following operating modes. High-attenuation three-phase VIIP filters rated up to

600VAC maintain power quality at the point of common coupling, keeping total harmonic voltage distortion within statutory limits defined by IEEE 519 standards. Direct factory engineering support from VIIP allows clean energy developers to configure optimized LC filter values, evaluate thermal dissipation under heavy continuous loads, and verify regulatory margins before deploying volume installations.

Technical Documentation and Direct Engineering Support

Energy storage developers, charging pile manufacturers, and power electronics engineers can access complete VIIP electrical specifications, mechanical dimension drawings, and insertion loss curves directly through the official international portal at <https://en.szviip.com/> to submit custom voltage and current requirements and request engineering evaluation samples.



Media Contact

SHENZHEN VIIP ELECTRONICS CO.,LTD.

*****@szviip.com

0755-29170376

Room 1301, Block B, Rongchao New Times Plaza, Guanlan High-Tech Industrial Park, Longhua District, Shenzhen. China

<https://en.szviip.com/>

Source : SHENZHEN VIIP ELECTRONICS CO.,LTD.

[See on IssueWire](#)

